

## PRODUCT SPECIFICATION SHEET



# 80/90 GEAR OIL

**PRODUCT # 10043, 10046,  
10066, 10067, 10069**

### TEST

### ASTM

### TYPICAL

<b>API Gravity</b>	<b>D-1298</b>	<b>25.0</b>
<b>Specific Gravity @ 60°F</b>	<b>D-1298</b>	<b>.9042</b>
<b>Density @ 60°F LBS/US Gal</b>	<b>D-1298</b>	<b>7.529</b>
<b>Viscosity @ 100°C cSt</b>	<b>D-445</b>	<b>15.0</b>
<b>Color</b>		<b>Clear Amber</b>
<b>Flash Point COC °C/F</b>	<b>D-92</b>	<b>415°</b>
<b>Odor</b>		<b>Characteristic Petroleum plus sulphur additives</b>
<b>AGMA Designation</b>		<b>4EP</b>
<b>Timken OK Load, Lbs</b>		<b>70</b>

## EXCEEDS ALL GL CLASSIFICATIONS

**Lucas 80/90 Gear Oil is a technical blend of oils and additives designed to give longer oil life and longer component life with less power draw. It is formulated with special anti-wear agents and anti-seize agents not found in common gear oils. It contains special lubricity agents for less wear, less heat, less power usage and longer bearing life.**

**Lucas 80/90 Gear Oil is formulated with special “climbing additives.” This action is especially important in power dividers and hypoid gears. It resists breakdown from contact with water. It will blend with other gear oils, even synthetics.**