

PRODUCT SPECIFICATION SHEET



SYNTHETIC 10W-30

PRODUCT # 10050, 10117, 10118, 10119, 10128
API Service SM/SL/SJ/CF

TEST

ASTM

TYPICAL

| | | |
|----------------------------------|---------------|--------------------|
| API Gravity | D-1298 | 33.2 |
| Specific Gravity @ 60°F | D-1298 | .8591 |
| Density @ 60°F LBS/US Gal | D-1298 | 7.153 |
| Viscosity @ 40°C | D-445 | 57.0 |
| Viscosity @ 100°C | D-445 | 10.5 |
| Viscosity Index | D-2270 | 185 |
| Color | | Light Brown |
| Flash Point COC °F | D-92 | 420° |
| Pour Point | D-97 | -35° |

This excellent product provides the consistent viscosity needed for precision ET racing. LUCAS Synthetic 10W-30 is a formulation of only the finest light synthetic base oils plus an exclusive additive package that includes lubricity agents and anti-seize agents that control drag like a zero weight oil and protect like a heavy multi-viscosity oil.

It's the perfect non-foaming lubricant for high RPM go-cart and motorcycle engines.

It's also excellent for normal highway use.

Lucas Synthetic 10W-30 is the perfect lubricant for extreme low temperatures or extreme high temperatures and blends with other synthetic or regular motor oil. Blend a quart or two into your conventional motor oil for easier starting and longer oil life.

Meets or exceeds all manufacturers specifications for SAE10W-30 and APISL and ILSACGF3. Exceeds A3/B3/B4 • SM/SL/SJ/CF.