

PRODUCT SPECIFICATION SHEET



X-TRA HEAVY DUTY GREASE

PRODUCT # 10301, 10305, 10316, 10335

PRODUCT # 10330

NLGI Grade: 2 GC-LB

TEST

ASTM

TYPICAL

Thickener Type		Polyurea
Texture		Smooth
Color		Green
Penetration Worked	D-2665	285
Dropping Point °F(°C) Min.	D-1831	500(260)
Water Washout % Loss Max	D-1264	10.0
Rust Prevention	D-1743	Pass
Copper Corrosion, Rating	D-4048	1b
Oxidation Stability, PSI Loss Max	D-942	5
Oil Separation % Loss, Max	D-1742	5.0
4-Ball		
Weld Point	D-2596	400
Load Wear Index, Kgf.	D-2596	50
Timken OK Load, Lbs	D-2509	60
Base Oil Characteristics		
Viscosity @ 100°C, cSt	D-445	14.5
@ 40°C, cSt	D-445	145
@ 210°F, SUS	D-445	65.0
@ 100°F, SUS	D-445	675
Viscosity Index		70

Lucas X-Tra Heavy Duty Grease is a shear stable product with exceptional extreme pressure characteristics and excellent water resistance. It's recommended for steel mills, off-road equipment, fleet and commercial applications. It has excellent mobility at low temperatures. It lasts four times longer in wheel bearing tests over conventional lithium grease, exceeds OEM "Lube For Life" specifications. Compatible with most other non-synthetic greases.